


## 150W Triple Output Series



- High reliability, low cost
- Built-in EMI filter
- 100% full load burn-in test
- Protections: over current/ short circuit
- V1 is isolated from the other outputs
- 1 year warranty
- F615 199 x 98 x 50(mm)

AC input voltage range .....	170~264VAC (210~370VDC)
Inrush current .....	cold start, 40A/230V
Input leakage current .....	< 0.7mA/ 230VAC
Line regulation (full load) .....	$\leq \pm 0.5\%$
Load regulation .....	$V_1: \leq \pm 0.5\%, V_2, V_3: \leq \pm 3\%$
Output voltage adjust range .....	$V_1: \pm 5\%$ of rated output voltage
Output over current protection .....	110~130%
Withstand voltage .....	I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise, Hold up time .....	50ms, 20ms@full load (typical)
Operating temp. & humidity .....	-10°C~+50°C, 20%~90%RH (non condensing)
Storage temp. & humidity .....	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards .....	design meet GB4943, UL60950, EN60950
EMC standards .....	design meet GB9254, EN55022 classA EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method .....	convection

Model	DC Output		R&N	Efficiency
HF150W-T-A	24V	1.0~5.0A	150mV	78%
	12V	0.0~2.5A	150mV	
	5V	0.0~2.0A	80mV	
HF150W-T-B	24V	1.0~5.0A	150mV	80%
	12V	0.0~2.5A	150mV	
	-12V	0.0~1.5A	120mV	

## Drawing

