

20W Dual Output Series



- High reliability, low cost
- Built-in EMI filter
- 100% full load burn-in test
- Protections: overload/ short circuit
- V1 is isolated from the other output
- 1 year warranty
- F602 111 x 78 x 36(mm)

AC input voltage range	170~264VAC (210~370VDC)
Inrush current	cold start, 30A/230V
Input leakage current	< 0.5mA/ 230VAC
Line regulation (full load)	≤ ± 0.5%
Load regulation	V ₁ : ≤ ± 0.5%, V ₂ : ≤ ± 3% (with regulator); ≤ ± 6% (without)
Output voltage adjust range	V ₁ : ± 5% of rated output voltage
Output overload protection	110~150%
Withstand voltage	I/P -O/P: 1.5KVAC/1min; I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise, Hold up time	50ms, 20ms@full load (typical)
Operating temp. & humidity	-10℃~+50℃, 20%~90%RH (non condensing)
Storage temp. & humidity	-20℃~+85℃, 20%~95%RH (non condensing)
Safety standards	design meet GB4943, UL60950, EN60950
EMC standards	design meet GB9254, EN55022 class A EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		R&N	Efficiency
HF20W-D-A	5V	0.4~3.0A	50mV	68%
	5V	0.2~1.5A	50mV	
HF20W-D-B	5V	0.4~3.0A	50mV	69%
	12V	0.0~1.0A	80mV	
HF20W-D-C	5V	0.4~3.0A	50mV	69%
	15V	0.0~1.0A	80mV	
HF20W-D-D	5V	0.4~3.0A	50mV	71%
	24V	0.1~0.7A	100mV	

Drawing

